



US005996431A

# United States Patent [19]

Pierse

[11] Patent Number: 5,996,431  
[45] Date of Patent: Dec. 7, 1999

## [54] TWIST ACTION FRICTION DRIVE

61038256 2/1986 Japan.

[75] Inventor: Michael George Pierse, Bedford,  
United Kingdom

## OTHER PUBLICATIONS

Marks' Standard Handbook For Mechanical Engineers, 10th  
Ed, pp. 8-130 to 8-131.

[73] Assignee: Unova U.K. Limited, Avlesbury,  
United Kingdom

Primary Examiner—Tamara L. Graysay  
Assistant Examiner—David Fenstermacher  
Attorney, Agent, or Firm—Lee, Mann, Smith, McWilliams,  
Sweeney & Ohlson

[21] Appl. No.: 09/051,248

[22] PCT Filed: Apr. 30, 1997

[86] PCT No.: PCT/GB97/01174

§ 371 Date: Apr. 2, 1998

§ 102(e) Date: Apr. 2, 1998

[87] PCT Pub. No.: WO98/10206

PCT Pub. Date: May 12, 1998

## [30] Foreign Application Priority Data

Sep. 6, 1996 [GB] United Kingdom ..... 9618642

[51] Int. Cl.<sup>6</sup> ..... F16H 21/16

[52] U.S. Cl. .... 74/25; 74/89

[58] Field of Search ..... 74/25, 89, 60;  
384/100

## [56] References Cited

### U.S. PATENT DOCUMENTS

4,203,328	5/1980	De Boynton	74/25
4,760,864	8/1988	Leclerc	74/25
4,921,207	5/1990	Baker	74/25
5,363,711	11/1994	Seto	74/25

### FOREIGN PATENT DOCUMENTS

30 05 147 2/1981 Germany.

17 Claims, 4 Drawing Sheets

## [57] ABSTRACT

A twist action roller friction drive comprises a rotating drive bar which drives in rotation a roller the axis of rotation of which is inclined relative to the axis of a rotationally fixed driven member with which the roller engages. The inclined roller comprises a single annular roller urged from the inside into driving contact with the driven member by one or more hydrostatic pads. The driven member is a tube and the skewed annular roller is in frictional engagement with the bore of the tube. In a typical use, the tube is fixed to the carriage of a machine tool and is aligned with the machine axis. Oil for the hydrostatic pad(s) acting on the roller is supplied through the drive bar along the axis thereof. At its trailing end, the drive bar rotationally drives a skewed roller assembly in which the annular roller is incorporated, the remote forward end of the drive bar being driven in rotation, as by an electric motor. Axial movement of the driven member is principally determined by the angle of skew of the roller so that if this angle is made very small, similarly small precise axial movements of the driven member of as little as 1 nm (nanometre) or less can be readily achieved, per revolution of the drive bar. This permits a high speed drive motor and in turn velocity feed back control.

